



Standard Unit



Parking
Management

A nearly plug&play device, is a combination of HD camera integrated with LPR algorithm and Mini-cloud software, LED display, flash LEDs, controller, housing and other components that can be applied to entrances, exits and zone gates. Different than a pole-mounted camera, this housed LPR camera can avoid wrongly focusing led by accidental contract. All settings can be downloaded and updated from either Mini-cloud platform or a premises server, which allows you to save a lot of time spent configuring that.

LED Display

- High brightness LED display
- License plate display
- Payment message display
- Red/Green/Orange color
- Dimension : 304 * 304 mm

LPR Camera

- 2 M pixels
- 2.8" (Motorized zoom)
- 1920 * 1080 resolution
- H.264/H265/MPEG
- Loop, Video trigger mode
- Port : RJ45 10/100Mbps & RS485
- I/O : Input * 4 Output * 2



Parameter

| | |
|--------------------|---|
| Rated Voltage: | 220 VAC 50 Hz |
| Power Consumption: | 100 W |
| IP Rate : | IP54 |
| Installation: | Ground |
| Material: | Steel |
| Temperature: | -10 ~ 50 °C |
| Humidity: | 30% ~ 80% No condensation |
| Color: | Dark Grey (Glass) Flash Silver (Cabinet) |

